

General Specifications

914N – Adjustable for spring sizes 1-4. Meets 5lbs., maximum opening force for interior doors, and 8.5lbs., maximum opening force for exterior doors.

936N – Adjustable for spring sizes 3-6 to meet a variety of on-site conditions.

Handing – Non-handed for regular, top jamb and parallel arm mount applications.

Adjusting Valves – Two non-critical adjusting valves (sweep and latch) work to provide consistent closing needs through a wide range of temperatures.

Packaging – 1 per box, 6 per master carton.

Warranty – 10 years.

Finish

Aluminum (689) AL, Dark Bronze (690) DBZ, Light Bronze (691) LBZ, Gold (696) GL and Black (693) BLK.



Certification & Compliance

- All 900N Series closers are UL and CUL listed for use on 3 hour or lesser doors. They conform to the requirements of ANSI A156.4, Grade1, and meet the requirements of UL10C and UBC7.2 (1997) for positive pressure.
- 914N closers meet the standard of ANSI A117.1 for barrier free accessibility.

Tri-pack configurations

Description	Part No.
Standard arm, sizes 1-4	914N
Standard arm, sizes 3-6	936N
Hold-open arm, sizes 1-4	914NH
Hold-open arm, sizes 3-6	936NH

Parts & accessories

Description	Part No.
Drop plate	936DP
914N Closer body	914BO
936N Closer body	936BO
Through-bolts for 1-3/8" thick door	5016TB38
Through-bolts for 1-3/4" thick door	5016TB34
Complete (tri-pack) standard arm assembly	5016CNA
Complete (tri-pack) hold-open arm assembly	5016CHA