



## General Specifications

**Chassis** – Non-ferrous alloy cover and base, 8-3/8" (212.72 mm) x 2" (50.8 mm) x 2-5/8" (66.67 mm). Tamper-proof cover screw sets unit into alarm upon unauthorized removal of the cover.

**Power/Electronics** – 9 volt battery powered. Modern, solid state electronics. Magnet activated.

**Doors** – For inward or outward swinging doors with 4" minimum stile.

**Alarm/Horn** – Alarm sounds for 2 minutes, shuts off and automatically rearms itself. Piercing, high frequency horn. Rated for 90 decibels at 6 feet.

**Cylinders** – Inside cylinder operation to arm or disarm unit using 1-1/8" (28.57 mm) mortise cylinder. Outside rim cylinder operation standard. (Order cylinders separately).

**Hand** – Non-handed.

### Features

**110 Series** – Push button test to determine available battery power.

**130 Series** – 15 second delay upon arming permits key holder to exit door without sounding alarm.

Low battery alert causes unit to chirp intermittently to indicate low battery power.

Red LED indicator flashes when violation occurs. Light continues to flash beyond alarm cycle and can only be turned off by the inside key.

### Finish

Powder coated painted finishes: AL BRZ, RD.

Hardware finishes: US10, US10B, US26, US26D.

## Exit Devices 300 series exit alarm

## General Specifications

**Chassis** – Paddle, chassis and cover made from a non-ferrous alloy. Cover 12-3/4" (323.85 mm) x 2" (50.8 mm) x 2-5/8" (66.67 mm); paddle projection 3-1/4" (88.25 mm); length to end of paddle 10-3/8" (263.52 mm).

**Power/Electronics** – 9 volt battery powered. Modern solid state electronics.

**Latch** – 3/4" (19.05 mm) latchbolt monitored by an electronic sensor switch. Any unauthorized movement of the latchbolt will cause unit to go into alarm.

**Doors** – For outward swinging doors 1-3/4" (44.45 mm) thick with a 4" minimum stile.

**Alarm/Horn** – Alarm sounds for 2 minutes, shuts off and automatically rearms itself. Piercing, dual frequency pulsating horns. Rated for 90 decibels at 6 feet.

**Cylinders** – Inside cylinder operation to arm or disarm unit using 1-1/8" (28.57 mm) mortise cylinder. (Order cylinder separately).

**Hand** – Reversible. Units are packed RHRB.

### Features

**Model 320** – Auto relatching.

Red LED indicator flashes when violation occurs. Light continues to flash beyond alarm cycle and can only be turned off by the inside key.

One chassis will accept all available trim options.

Unit must be activated to test available battery power.

**Model 330** – Contains same features as the 320.

Low battery alert feature causes unit to chirp intermittently to indicate low battery power.

### Finish

Powder coated painted finishes: AL, BRZ, RD.

Hardware finishes: US10, US10B, US26, US26D.

### Certification & Compliance

UL listed. Designed to meet ANSI 156.5-1984 and A117.1-1980 for Accessibility Standards.

